

PDFVCE



Choose the version that fits your needs	PDF Version	Desktop Test Engine	Online Test Engine
Latest and Up-to-Date exam dumps with real exam questions answers.	✓	✓	✓
Get 12-Months free updates without any extra charges.	✓	✓	✓
Experience same exam environment before appearing in the certification exam.	✗	✓	✓
100% exam passing guarantee in the first attempt.	✓	✓	✓
20% discount on more than one license and 30% discount on 5+ license purchases.	✗	✓	✓
100% secure purchase on SSL.	✓	✓	✓
Completely private purchase without sharing your personal info with anyone.	✓	✓	✓

<http://www.pdfvce.com>

Highly Efficiently Exam Tool and Effective Exam Practice Materials

Exam : **CWDP-303**

Title : Certified Wireless Design
Professional

Vendor : CWNP

Version : DEMO

NO.1 What is the minimum PoE budget needed on a switch to support 6 (six) APs that can only be powered using IEEE 802.3at if no other details are provided?

- A. 320 W
- B. 60 W
- C. 180 W
- D. 240 W

Answer: B

NO.2 During an RFP analysis, one of the vendors mentioned that you'll need to upgrade your Gigabit Ethernet switches to MultiGig switches to ensure support for 802.11ac and 802.11ax, which both offer data rates over 1Gbps. Why is this not sound advice?

- A. Management overhead that is normal in WLANs will reduce the throughput of the client devices
- B. Because neither of the technologies support data rates over 1Gbps
- C. Because 802.11ax doesn't support channel bonding
- D. Because 802.11ac only supports one spatial stream

Answer: A

NO.3 You're about to deploy an Enterprise-class VoWLAN infrastructure. You need to ensure that QoS is properly configured throughout the network. What Access Category (AC) should voice frames/packets use?

- A. AC_VI
- B. AC_BE
- C. AC_VO
- D. AC_BK

Answer: C

NO.4 A controller-based WLAN infrastructure has its controller on a different subnet than its APs. What device must be used to enable any communication between the Controller and the APs?

- A. PoE Layer 2 switch
- B. NTP server
- C. Router
- D. Wireless bridge

Answer: C

NO.5 When using a predictive design tool, you have selected APs with an antenna gain 3 dBi and set the transmit power of the predicted APs to 25 mW. What should be EIRP of the APs in the design?

- A. 6.25 mW
- B. 11 dBm
- C. 17 dBm
- D. 125 mW

Answer: C

NO.6 When installing APs on high ceilings, what should be the most common PPE to be used?

- A.** Clean suits, masks and glasses
- B.** Glasses, gloves and jacket
- C.** Hardhat, high visibility vest and body belt
- D.** Clean suits, gloves and jacket

Answer: C